

YET 203-008



Insert bearings are based on sealed deep groove ball bearings. This variant is intended for use in applications where the direction of rotation is constant. It has a narrow inner ring extended on one side, with an eccentric locking collar, enabling quick and easy mounting onto the shaft.

- Designed for rotation in one direction
- Quick and easy to mount onto the shaft
- Long service life
- Reduce noise and vibration levels



Dimensions		
d	12.7 mm	Bore diameter
D	40 mm	Outside diameter
B ₁	28.6 mm	Overall bearing width
B	19.1 mm	Width of inner ring
C	12 mm	Width of outer ring
d ₁	≈ 24.2 mm	Outside diameter of inner ring
d ₂	27.2 mm	Outside diameter of locking collar
B ₄	4.75 mm	Distance from side face to thread centre
r _{1,2}	min. 0.3 mm	Chamfer dimension of inner ring
s ₁	22.1 mm	Distance from locking device side face to raceway centre

Calculation data

Basic dynamic load rating	C	9.56 kN
Basic static load rating	C ₀	4.75 kN
Fatigue load limit	P _u	0.2 kN

Limiting speed	9 500 r/min
----------------	-------------

Limiting speed with shaft
tolerance h6

Calculation factor	f_0	13
--------------------	-------	----

Mounting information

Set screw	G ₂	1/4-28 UNF
-----------	----------------	------------

Hexagonal key size for set screw	N	3.175 mm
----------------------------------	---	----------

Recommended tightening torque for set screw	4 N·m
---	-------

Associated products

Rubber seating ring	RIS 203
---------------------	---------

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table 1, table 2
- Radial internal clearance: Standard inner ring, Other bearings

BEARING INTERFACES

- Shaft tolerances