


QJ 216 MA




Four-point contact ball bearings can accommodate high axial loads in both directions and small radial loads. They can operate at very high speeds and are more suitable than deep groove ball bearings for supporting large axial forces. The outer ring, with ball and cage assembly, can be mounted separately from the two inner ring halves.

- High-speed capability
- Accommodate high axial loads in both directions and small radial loads
- Require considerably less axial space than double row angular contact ball bearings



Dimensions		
d	80 mm	Bore diameter
D	140 mm	Outside diameter
B	26 mm	Width
d ₁	≈ 95.3 mm	Shoulder diameter inner ring
D ₁	≈ 120 mm	Shoulder diameter outer ring/ inner diameter housing washer
a	77 mm	Distance pressure point(s)
r _{1,2}	min. 2 mm	Chamfer dimension inner ring



Abutment dimensions		
d _a	min. 91 mm	Abutment diameter shaft
D _a	max. 130 mm	Abutment diameter housing
r _a	max. 2 mm	Fillet radius

Calculation data

performance class		Explorer
Basic dynamic load rating	C	146 kN
Basic static load rating	C ₀	156 kN
Fatigue load limit	P _u	6.4 kN
Limiting speed		8 000 r/min
Calculation factor	A	0.0629
Limiting value	e	0.95
Calculation factor	X	0.6
Calculation factor	Y ₀	0.58
Calculation factor	Y ₁	0.66
Calculation factor	Y ₂	1.07

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6
- Internal clearance: table

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit