


3220 A


Double row angular contact ball bearings correspond, in their design and operation, to a pair of single row angular contact ball bearings in a back-to-back arrangement, while requiring less axial space. They can operate at high speeds and are more suitable than deep groove ball bearings for supporting large axial forces in both directions.



- High-speed capability
- Accommodate relatively high radial loads, high axial loads in both directions and tilting moments
- Suitable where a stiff bearing arrangement is required
- Require less axial space than equivalent pair of single row angular contact ball bearings



Dimensions		
d	100 mm	Bore diameter
D	180 mm	Outside diameter
B	60.3 mm	Width
d ₁	≈ 126.55 mm	Shoulder diameter inner ring
D ₁	≈ 161.05 mm	Shoulder diameter outer ring
r _{1,2}	min. 2.1 mm	Chamfer dimension inner ring
a	107 mm	Distance pressure point(s)



Abutment dimensions		
d _a	min. 112 mm	Abutment diameter shaft
D _a	max. 168 mm	Abutment diameter housing
r _a	max. 2 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	178 kN
Basic static load rating	C ₀	166 kN
Fatigue load limit	P _u	6 kN
Reference speed		3 800 r/min
Limiting speed		3 200 r/min
Calculation factor	k _r	0.06
Limiting value	e	0.8
Calculation factor	X	0.63
Calculation factor	Y ₀	0.66
Calculation factor	Y ₁	0.78
Calculation factor	Y ₂	1.24

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5
- Internal clearance: table, drawing no

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit