

7221 BECBP




These single row angular contact ball bearings can accommodate radial and axial loads acting simultaneously, where the axial load acts in one direction only. They can operate at high speeds and, depending on the variant, even very high speeds. They are more suitable than deep groove ball bearings for supporting large axial forces acting in one direction.

- High-speed capability
- Accommodate relatively high radial loads and large unilateral axial loads



Dimensions		
d	105 mm	Bore diameter
D	190 mm	Outside diameter
B	36 mm	Width
d ₁	≈ 137.95 mm	Shoulder diameter of inner ring (large side face)
d ₂	≈ 121.17 mm	Shoulder diameter of inner ring (small side face)
D ₁	≈ 159.1 mm	Shoulder diameter of outer ring (large side face)
a	80 mm	Distance side face to pressure point
r _{1,2}	min. 2.1 mm	Chamfer dimension
r _{3,4}	min. 1.1 mm	Chamfer dimension



Abutment dimensions		
d _a	min. 117 mm	Diameter of shaft abutment
D _a	max. 178 mm	Abutment diameter housing
D _b	max. 183 mm	Diameter of housing abutment
r _a	max. 2 mm	Radius of fillet
r _b	max. 1 mm	Radius of fillet

Calculation data

performance class		Explorer
Basic dynamic load rating	C	156 kN
Basic static load rating	C ₀	150 kN
Fatigue load limit	P _u	5.2 kN
Reference speed		4 000 r/min
Limiting speed		4 300 r/min
Minimum axial load factor	A	0.302
Minimum radial load factor	k _r	0.095
Limiting value	e	1.14

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, P5, Normal (inch)
- Internal clearance: CA+CB+CC, G
- Preload: GA+GB+GC

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit