

7204 BECBY



These single row angular contact ball bearings can accommodate radial and axial loads acting simultaneously, where the axial load acts in one direction only. They can operate at high speeds and, depending on the variant, even very high speeds. They are more suitable than deep groove ball bearings for supporting large axial forces acting in one direction.

- High-speed capability
- Accommodate relatively high radial loads and large unilateral axial loads



Dimensions		
d	20 mm	Bore diameter
D	47 mm	Outside diameter
B	14 mm	Width
d ₁	≈ 30.85 mm	Shoulder diameter of inner ring (large side face)
d ₂	≈ 25.87 mm	Shoulder diameter of inner ring (small side face)
D ₁	≈ 36.5 mm	Shoulder diameter of outer ring (large side face)
a	21 mm	Distance side face to pressure point
r _{1,2}	min. 1 mm	Chamfer dimension
r _{3,4}	min. 0.6 mm	Chamfer dimension



Abutment dimensions		
d _a	min. 25.6 mm	Diameter of shaft abutment
D _a	max. 41.4 mm	Abutment diameter housing
D _b	max. 42.8 mm	Diameter of housing abutment
r _a	max. 1 mm	Radius of fillet
r _b	max. 0.6 mm	Radius of fillet

Calculation data

performance class		Explorer
Basic dynamic load rating	C	14.3 kN
Basic static load rating	C ₀	8.15 kN
Fatigue load limit	P _u	0.345 kN
Reference speed		19 000 r/min
Limiting speed		19 000 r/min
Minimum axial load factor	A	0.00113
Minimum radial load factor	k _r	0.095
Limiting value	e	1.14

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, P5, Normal (inch)
- Internal clearance: CA+CB+CC, G
- Preload: GA+GB+GC

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit