

6330/C3VL2071



INSOCOAT single row deep groove ball bearings feature an electrically insulating coating on the outside surfaces of either the inner or outer bearing ring. This keeps stray electric currents from passing through the bearings, protecting them against electrical erosion damage and helping prevent lubricant degradation resulting from electric current discharge. As with deep groove ball bearings generally, they are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

- Coating protects against electrical erosion damage
- Reduced lubricant degradation resulting from electric current discharge
- Typical benefits of single row deep groove ball bearings

Dimensions	
Bore diameter	150 mm
Outside diameter	320 mm
Width	65 mm
Performance	
Basic dynamic load rating	286 kN
Basic static load rating	285 kN
Reference speed	4 300 r/min
Limiting speed	2 800 r/min
Properties	
Filling slots	Without
Number of rows	1

Locating feature, bearing outer ring	None
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	C3
Material, bearing	Bearing steel
Coating	Insulation coating on inner ring
Sealing	Without
Lubricant	None
Relubrication feature	Without
Logistics	
Product net weight	22.7 kg
eClass code	23-05-09-01
UNSPSC code	31171537