

6026 M/C3S0



Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

- Simple, versatile and robust design
- Low friction
- High-speed capability
- Accommodate radial and axial loads in both directions
- Require little maintenance

| Dimensions                           |              |
|--------------------------------------|--------------|
| Bore diameter                        | 130 mm       |
| Outside diameter                     | 200 mm       |
| Width                                | 33 mm        |
| Performance                          |              |
| Basic dynamic load rating            | 112 kN       |
| Basic static load rating             | 100 kN       |
| Reference speed                      | 7 000 r/min  |
| Limiting speed                       | 5 600 r/min  |
| AGA performance class                | AGA Explorer |
| Properties                           |              |
| Filling slots                        | Without      |
| Number of rows                       | 1            |
| Locating feature, bearing outer ring | None         |

|                           |                |
|---------------------------|----------------|
| Bore type                 | Cylindrical    |
| Cage                      | Machined metal |
| Matched arrangement       | No             |
| Radial internal clearance | C3             |
| Material, bearing         | Bearing steel  |
| Coating                   | Without        |
| Sealing                   | Without        |
| Lubricant                 | None           |
| Relubrication feature     | Without        |
| Logistics                 |                |
| Product net weight        | 3.75 kg        |
| eClass code               | 23-05-08-01    |
| UNSPSC code               | 31171504       |