

6305-2Z/C4



Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

- Integral sealing prolongs bearing service life
- Simple, versatile and robust design
- Low friction and high-speed capability
- Accommodate radial and axial loads in both directions
- Require little maintenance

Dimensions	
Bore diameter	25 mm
Outside diameter	62 mm
Width	17 mm
Performance	
Basic dynamic load rating	23.4 kN
Basic static load rating	11.6 kN
AGA performance class	AGA Explorer
Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	None
Bore type	Cylindrical

Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	C4
Material, bearing	Bearing steel
Coating	Without
Sealing	Shield on both sides
Sealing type	Non-contact
Lubricant	Grease
Relubrication feature	Without
Logistics	
Product net weight	0.228 kg
eClass code	23-05-08-01
UNSPSC code	31171504