

6224 M/C3



Single row deep groove ball bearings are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types.

- Simple, versatile and robust design
- Low friction
- High-speed capability
- Accommodate radial and axial loads in both directions
- Require little maintenance

| Dimensions                           |             |
|--------------------------------------|-------------|
| Bore diameter                        | 120 mm      |
| Outside diameter                     | 215 mm      |
| Width                                | 40 mm       |
| Performance                          |             |
| Basic dynamic load rating            | 146 kN      |
| Basic static load rating             | 118 kN      |
| Reference speed                      | 6 300 r/min |
| Limiting speed                       | 5 600 r/min |
| Properties                           |             |
| Filling slots                        | Without     |
| Number of rows                       | 1           |
| Locating feature, bearing outer ring | None        |
| Bore type                            | Cylindrical |

|                           |                |
|---------------------------|----------------|
| Cage                      | Machined metal |
| Matched arrangement       | No             |
| Radial internal clearance | C3             |
| Material, bearing         | Bearing steel  |
| Coating                   | Without        |
| Sealing                   | Without        |
| Lubricant                 | None           |
| Relubrication feature     | Without        |
| Logistics                 |                |
| Product net weight        | 6.33 kg        |
| eClass code               | 23-05-08-01    |
| UNSPSC code               | 31171504       |