

6316-RS1



Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

- Integral sealing prolongs bearing service life
- Simple, versatile and robust design
- Low friction and high-speed capability
- Accommodate radial and axial loads in both directions
- Require little maintenance

Dimensions	
Bore diameter	80 mm
Outside diameter	170 mm
Width	39 mm
Performance	
Basic dynamic load rating	130 kN
Basic static load rating	86.5 kN
Limiting speed	2 600 r/min
AGA performance class	AGA Explorer
Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	None

Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on one side
Sealing type	Contact
Lubricant	None
Relubrication feature	Without
Logistics	
Product net weight	3.56 kg
eClass code	23-05-08-01
UNSPSC code	31171504