

6312-RS1Z/C4GJN4



Single row deep groove ball bearings with seals or shields are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

- Integral sealing prolongs bearing service life
- Simple, versatile and robust design
- Low friction and high-speed capability
- Accommodate radial and axial loads in both directions
- Require little maintenance

| Dimensions                           |              |
|--------------------------------------|--------------|
| Bore diameter                        | 60 mm        |
| Outside diameter                     | 130 mm       |
| Width                                | 31 mm        |
| Performance                          |              |
| Basic dynamic load rating            | 85.2 kN      |
| Basic static load rating             | 52 kN        |
| Limiting speed                       | 3 400 r/min  |
| AGA performance class                | AGA Explorer |
| Properties                           |              |
| Filling slots                        | Without      |
| Number of rows                       | 1            |
| Locating feature, bearing outer ring | None         |

|                           |                                       |
|---------------------------|---------------------------------------|
| Bore type                 | Cylindrical                           |
| Cage                      | Sheet metal                           |
| Matched arrangement       | No                                    |
| Radial internal clearance | C4                                    |
| Material, bearing         | Bearing steel                         |
| Coating                   | Without                               |
| Sealing                   | Seal on one side, shield on the other |
| Sealing type              | Contact                               |
| Lubricant                 | Grease                                |
| Relubrication feature     | Without                               |
| Logistics                 |                                       |
| Product net weight        | 1.74 kg                               |
| eClass code               | 23-05-08-01                           |
| UNSPSC code               | 31171504                              |