

6207-2RS1N



Single row deep groove ball bearing with snap ring groove and seals or shields on one or both sides are particularly versatile, have low friction and are optimized for low noise and low vibration, which enables high rotational speeds. They accommodate radial and axial loads in both directions, are easy to mount, and require less maintenance than many other bearing types. An annular groove in the outer ring enables the bearings to retain a snap ring. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

- Can accommodate a snap ring
- Integral sealing prolongs bearing service life
- Typical benefits of single row deep groove ball bearings

Dimensions	
Bore diameter	35 mm
Outside diameter	72 mm
Width	17 mm
Performance	
Basic dynamic load rating	27 kN
Basic static load rating	15.3 kN
Limiting speed	6 300 r/min
AGA performance class	AGA Explorer
Properties	
Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	Snap ring groove

Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	CN
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	Without
Logistics	
Product net weight	0.286 kg
eClass code	23-05-08-01
UNSPSC code	31171504