

6010-2Z/HC5C3WT



Hybrid ceramic single row deep groove ball bearings have rings made of bearing steel and rolling elements made of bearing grade silicon nitride, which make the bearings electrically insulating. The integral shields can significantly prolong bearing service life because they keep lubricant in the bearings and contaminants out. The ceramic rolling elements not only provide protection from electric current damage but also, when compared to same-sized bearings with steel rolling elements, provide enhanced bearing performance, extended bearing service life, higher speed capability, high wear-resistance, high bearing stiffness, reduced risk of smearing and false brinelling, and less sensitivity to temperature gradients, making them suitable for use in difficult conditions and contaminated environments.

- Protected against electric current damage
- Integral shields prolong bearing service life
- Especially suited for use in difficult conditions and contaminated environments
- Typical benefits of single row deep groove ball bearings

Dimensions	
Bore diameter	50 mm
Outside diameter	80 mm
Width	16 mm
Performance	
Basic dynamic load rating	21.6 kN
Basic static load rating	15.6 kN
Reference speed	20 000 r/min
Limiting speed	11 000 r/min
Properties	

Filling slots	Without
Number of rows	1
Locating feature, bearing outer ring	None
Bore type	Cylindrical
Cage	Sheet metal
Matched arrangement	No
Radial internal clearance	C3
Material, bearing	Hybrid (ceramic balls)
Coating	Without
Sealing	Shield on both sides
Sealing type	Non-contact
Lubricant	Grease
Relubrication feature	Without
Logistics	
Product net weight	0.255 kg
eClass code	23-05-08-01
UNSPSC code	31171504