

51210

Single direction thrust ball bearings can accommodate axial loads in one direction. They must not be subjected to any radial load. Their separable components facilitate mounting/dismounting and maintenance inspections. Many of the components are interchangeable. The shaft washers have a ground bore that enables an interference fit.



- Separable design facilitates mounting/dismounting and maintenance inspections
- Interchangeable components
- Ground bore of shaft washers enable interference fit



Dimensions		
d	50 mm	Bore diameter
D	78 mm	Outside diameter
H	22 mm	Height
d ₁	≈ 78 mm	Outside diameter shaft washer
D ₁	≈ 52 mm	Inner diameter housing washer
r _{1,2}	min. 1 mm	Chamfer dimension washer



Abutment dimensions		
d _a	min. 67 mm	Abutment diameter shaft
D _a	max. 61 mm	Abutment diameter housing
r _a	max. 1 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	49.4 kN
---------------------------	---	---------

Basic static load rating	C ₀	116 kN
Fatigue load limit	P _u	4.3 kN
Reference speed		3 400 r/min
Limiting speed		4 500 r/min
Minimum load factor	A	0.069

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table 1

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit