

KDN.K16008XP0

Four-point contact ball bearings can accommodate radial, axial and moment loads simultaneously. One bearing series is based on a single cross section which remains constant as the bore diameter increases, leading to significant space and weight savings. The bearings are available with or inch main dimensions. Depending on the design and series the bearings can be provided with chemical and corrosion resistance.



- Accommodate radial, axial and moment loads simultaneously
- Require considerably less axial space than two angular contact ball bearings
- Thin cross section
- Lightweight
- Low friction
- High stiffness
- High running accuracy



Dimensions		
d	160 mm	Bore diameter
D	176 mm	Outside diameter
H	8 mm	Radial cross section
B	8.001 mm	Width
d ₁	≈ 165.9 mm	Shoulder diameter inner ring
D ₁	≈ 170.1 mm	Shoulder diameter outer ring
	3.969 mm	Ball diameter
	0.8 mm	Maximum radius of shaft or housing fillet

Calculation data

Dynamic load rating, Kaydon, radial direction	C _k	8.61 kN
Basic static load rating, radial direction	C ₀	16.3 kN

Basic static load rating, axial direction	C_{0a}	40.9 kN
Basic dynamic load rating, moment	C_M	0.543 kN·m
Basic static load rating, moment	C_{0M}	1.373 kN·m

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances, radial clearance and recommended fits:
 - Endurakote bearings: Class 1, Class 1, Class 3, Class 4
 - bearings: Class 1
 - other bearings: Class 1, Class 1, Class 3, Class 4, Class 6
- Materials

AGA BEARINGS