


Radial contact ball bearings with seals or shields are designed to accommodate radial loads and some axial loads in either direction. One bearing series is based on a single cross section which remains constant as the bore diameter increases, leading to significant space and weight savings. The bearings are available with inch and metric boundary dimensions. Depending on the design and series the bearings can be provided with chemical and corrosion resistance.

- Accommodate radial and some axial loads in both directions
- Thin cross section
- Lightweight
- Low friction
- High stiffness
- High running accuracy



| Dimensions     |              |                                           |
|----------------|--------------|-------------------------------------------|
| d              | 107.95 mm    | Bore diameter                             |
| D              | 123.825 mm   | Outside diameter                          |
| H              | 7.938 mm     | Radial cross section                      |
| B              | 7.938 mm     | Width                                     |
| d <sub>1</sub> | ≈ 113.817 mm | Shoulder diameter inner ring              |
| D <sub>1</sub> | ≈ 117.932 mm | Shoulder diameter outer ring              |
|                | 3.969 mm     | Ball diameter                             |
|                | 1.016 mm     | Maximum radius of shaft or housing fillet |

### Calculation data

|                                               |       |         |
|-----------------------------------------------|-------|---------|
| Dynamic load rating, Kaydon, radial direction | $C_K$ | 3.76 kN |
| Basic static load rating, radial direction    | $C_0$ | 8.14 kN |

## Tolerances and clearances

### GENERAL BEARING SPECIFICATIONS

- Tolerances, radial clearance and recommended fits:
  - Endurakote bearings: Class 1, Class 1, Class 3, Class 4
  - bearings: Class 1
  - other bearings: Class 1, Class 1, Class 3, Class 4, Class 6
- Materials

AGA BEARINGS