

KDN.K10020XP0

Four-point contact ball bearings can accommodate radial, axial and moment loads simultaneously. One bearing series is based on a single cross section which remains constant as the bore diameter increases, leading to significant space and weight savings. The bearings are available with or inch main dimensions. Depending on the design and series the bearings can be provided with chemical and corrosion resistance.



- Accommodate radial, axial and moment loads simultaneously
- Require considerably less axial space than two angular contact ball bearings
- Thin cross section
- Lightweight
- Low friction
- High stiffness
- High running accuracy



Dimensions		
d	100 mm	Bore diameter
D	140 mm	Outside diameter
H	20 mm	Radial cross section
B	20 mm	Width
d ₁	≈ 115 mm	Shoulder diameter inner ring
D ₁	≈ 125 mm	Shoulder diameter outer ring
	9.525 mm	Ball diameter
	1.5 mm	Maximum radius of shaft or housing fillet

Calculation data

Dynamic load rating, Kaydon, radial direction	C _k	22.8 kN
Basic static load rating, radial direction	C ₀	25.7 kN

Basic static load rating, axial direction	C_{0a}	64.2 kN
Basic dynamic load rating, moment	C_M	1.026 kN·m
Basic static load rating, moment	C_{0M}	1.54 kN·m

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances, radial clearance and recommended fits:
 - Endurakote bearings: Class 1, Class 1, Class 3, Class 4
 - bearings: Class 1
 - other bearings: Class 1, Class 1, Class 3, Class 4, Class 6
- Materials

AGA BEARINGS