


KDN.J05008XP0

Four-point contact ball bearings with seals or shields can accommodate radial, axial and moment loads simultaneously. One bearing series is based on a single cross section which remains constant as the bore diameter increases, leading to significant space and weight savings. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out. The bearings are available with and inch boundary dimensions.



- Accommodate radial, axial and moment loads simultaneously
- Require considerably less axial space than two angular contact ball bearings
- Integral sealing prolongs bearing service life
- Thin cross section
- Lightweight
- Low friction
- High stiffness
- High running accuracy



Dimensions		
d	50 mm	Bore diameter
D	66 mm	Outside diameter
H	8 mm	Radial cross section
B	8 mm	Width
d ₂	≈ 56.55 mm	Recess diameter inner ring
D ₂	≈ 59.42 mm	Recess diameter outer ring
	3.969 mm	Ball diameter
	0.8 mm	Maximum radius of shaft or housing fillet

Calculation data

Dynamic load rating, Kaydon, radial direction	C _K	4.51 kN
---	----------------	---------

Basic static load rating, radial direction	C_0	5.44 kN
Basic static load rating, axial direction	C_{0a}	13.6 kN
Basic dynamic load rating, moment	C_M	0.098 kN·m
Basic static load rating, moment	C_{0M}	0.158 kN·m
Starting torque max. no load		0.04 N·m
Limiting speed		1 500 r/min

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances, radial clearance and recommended fits:
 - Endurakote bearings: Class 1, Class 1, Class 3, Class 4
 - bearings: Class 1
 - other bearings: Class 1, Class 1, Class 3, Class 4, Class 6
- Materials