

C 30/900 KMB/VE635


CARB toroidal roller bearings are unique: as well as accommodating misalignment without increased stress levels, they also provide frictionless axial movement within the bearing in the non-locating position in self-aligning bearing arrangements. Being NR Explorer bearings, they can accommodate higher load levels and provide significantly extended service life.



- Accommodates misalignment and axial displacement within the bearing
- High radial load carrying capacity
- Provides frictionless axial movement
- Long bearing system life
- Reduce noise and vibration levels

Bore type

Tapered 1:12



Dimensions		
d	900 mm	Bore diameter
D	1 280 mm	Outside diameter
B	280 mm	Width
d ₂	≈ 1 004 mm	Shoulder diameter of inner ring
D ₁	≈ 1 173 mm	Shoulder or recess diameter of outer ring
s ₁	max. 25.5 mm	Permissible axial displacement
r _{1,2}	min. 7.5 mm	Chamfer dimension



Abutment dimensions		
da	min. 915 mm	Diameter of shaft abutment
da	max. 1 002 mm	Diameter of shaft abutment
Da	min. 1 124 mm	Diameter of housing abutment
Da	max. 1 252 mm	Abutment diameter housing

C_a	min. 3.3 mm	Minimum width of space required in housing
r_a	max. 6 mm	Radius of fillet
A negative value for C_a is theoretical.		

Calculation data

AGA performance class	AGA Explorer	
Basic dynamic load rating	C	12 700 kN
Basic static load rating	C_0	26 500 kN
Fatigue load limit	P_u	1 530 kN
Reference speed		300 r/min
Limiting speed		400 r/min
Misalignment factor	k_1	0
Internal clearance factor	k_2	0.1

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit