


C 5913 V/C4



CARB toroidal roller bearings are unique: as well as accommodating misalignment without increased stress levels, they also provide frictionless axial movement within the bearing in the non-locating position in self-aligning bearing arrangements. This full complement bearing, which has a lower speed rating, uses as many rollers as possible, giving it the highest possible load rating.

- Accommodate misalignment and axial displacement within the bearing
- Very high radial load carrying capacity
- Provide frictionless axial movement
- Long bearing system life

Bore type	Cylindrical	
	Dimensions	
	d	65 mm Bore diameter
	D	90 mm Outside diameter
	B	34 mm Width
	d ₂	≈ 72.8 mm Shoulder diameter of inner ring
	D ₁	≈ 82.7 mm Shoulder or recess diameter of outer ring
	s ₁	max. 6 mm Permissible axial displacement
	s ₂	max. 2.8 mm Permissible axial displacement
	r _{1,2}	min. 1 mm Chamfer dimension



Abutment dimensions		
d _a	min. 69.6 mm	Diameter of shaft abutment
d _a	max. 76 mm	Diameter of shaft abutment
D _a	max. 85.4 mm	Abutment diameter housing
r _a	max. 1 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	156 kN
Basic static load rating	C ₀	260 kN
Fatigue load limit	P _u	30.5 kN
Limiting speed		2 200 r/min
Misalignment factor	k ₁	0.113
Internal clearance factor	k ₂	0.097

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit