

C 3996 M

CARB toroidal roller bearings are unique: as well as accommodating misalignment without increased stress levels, they also provide frictionless axial movement within the bearing in the non-locating position in self-aligning bearing arrangements. Being NR Explorer bearings, they can accommodate higher load levels and provide significantly extended service life.



- Accommodate misalignment and axial displacement within the bearing
- High radial load carrying capacity
- Provide frictionless axial movement
- Long bearing system life
- Reduce noise and vibration levels


Bore type

Cylindrical



Dimensions

d	480 mm	Bore diameter
D	650 mm	Outside diameter
B	128 mm	Width
d ₂	≈ 528 mm	Shoulder diameter of inner ring
D ₁	≈ 604 mm	Shoulder or recess diameter of outer ring
s ₁	max. 20.4 mm	Permissible axial displacement
r _{1,2}	min. 5 mm	Chamfer dimension



Abutment dimensions

d _a	min. 498 mm	Diameter of shaft abutment
d _a	max. 552 mm	Diameter of shaft abutment
D _a	min. 585 mm	Diameter of housing abutment
D _a	max. 632 mm	Abutment diameter housing

C_a	min. 2 mm	Minimum width of space required in housing
r_a	max. 4 mm	Radius of fillet
A negative value for C_a is theoretical.		

Calculation data

AGA performance class	AGA Explorer	
Basic dynamic load rating	C	3 100 kN
Basic static load rating	C_0	6 100 kN
Fatigue load limit	P_u	425 kN
Reference speed		750 r/min
Limiting speed		1 000 r/min
Misalignment factor	k_1	0.133
Internal clearance factor	k_2	0.095

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit