

C 3136 K

CARB toroidal roller bearings are unique: as well as accommodating misalignment without increased stress levels, they also provide frictionless axial movement within the bearing in the non-locating position in self-aligning bearing arrangements. Being NR Explorer bearings, they can accommodate higher load levels and provide significantly extended service life.



- Accommodate misalignment and axial displacement within the bearing
- High radial load carrying capacity
- Provide frictionless axial movement
- Long bearing system life
- Reduce noise and vibration levels

Bore type

Tapered 1:12



Dimensions		
d	180 mm	Bore diameter
D	300 mm	Outside diameter
B	96 mm	Width
d ₂	≈ 210 mm	Shoulder diameter of inner ring
D ₁	≈ 266 mm	Shoulder or recess diameter of outer ring
s ₁	max. 23.2 mm	Permissible axial displacement
r _{1,2}	min. 3 mm	Chamfer dimension



Abutment dimensions		
Da	min. 252 mm	Diameter of housing abutment
Da	max. 286 mm	Abutment diameter housing
Ca	min. 2.2 mm	Minimum width of space required in housing
ra	max. 2.5 mm	Radius of fillet

A negative value for C_a is theoretical.

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	1 250 kN
Basic static load rating	C_0	1 730 kN
Fatigue load limit	P_u	156 kN
Reference speed		1 700 r/min
Limiting speed		2 400 r/min
Misalignment factor	k_1	0.102
Internal clearance factor	k_2	0.111

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit