

C 4032 K30

CARB toroidal roller bearings are unique: as well as accommodating misalignment without increased stress levels, they also provide frictionless axial movement within the bearing in the non-locating position in self-aligning bearing arrangements. Being NR Explorer bearings, they can accommodate higher load levels and provide significantly extended service life.



- Accommodate misalignment and axial displacement within the bearing
- High radial load carrying capacity
- Provide frictionless axial movement
- Long bearing system life
- Reduce noise and vibration levels

Bore type

Tapered 1:30



Dimensions		
d	160 mm	Bore diameter
D	240 mm	Outside diameter
B	80 mm	Width
d ₂	≈ 181 mm	Shoulder diameter of inner ring
D ₁	≈ 217 mm	Shoulder or recess diameter of outer ring
s ₁	max. 18.1 mm	Permissible axial displacement
r _{1,2}	min. 2.1 mm	Chamfer dimension



Abutment dimensions		
D _a	min. 209 mm	Diameter of housing abutment
D _a	max. 229 mm	Abutment diameter housing
C _a	min. 2.2 mm	Minimum width of space required in housing
r _a	max. 2 mm	Radius of fillet

A negative value for C_a is theoretical.

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	765 kN
Basic static load rating	C_0	1 160 kN
Fatigue load limit	P_u	110 kN
Reference speed		1 700 r/min
Limiting speed		2 400 r/min
Misalignment factor	k_1	0.109
Internal clearance factor	k_2	0.103

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit