

RNA 4856

Single row needle roller bearings without an inner ring consist of an outer ring with a needle roller and cage assembly. They are an excellent choice for compact bearing arrangements in applications where hardened and ground raceways can be provided on the shaft. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication.



- High radial load carrying capacity
- High stiffness
- Low cross-sectional height
- Accommodate axial displacement in both directions



Dimensions		
F _w	305 mm	Diameter under rollers
D	350 mm	Outside diameter
C	69 mm	Width
r _{1,2}	min. 2 mm	Chamfer dimension outer ring



Abutment dimensions		
D _a	max. 341 mm	Diameter of housing abutment
r _a	max. 2 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	429 kN
Basic static load rating	C ₀	1 320 kN

Fatigue load limit	P_u	129 kN
Reference speed		1 300 r/min
Limiting speed		1 400 r/min



Associated seals	
Available on request	Radial shaft seal

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5, ISO - F6 (F_w)
- Radial internal clearance: table

DESIGN CONSIDERATIONS

- Housing tolerances: table
- Shaft tolerances: Operating clearance