

NK 65/35



Single row needle roller bearings without an inner ring consist of an outer ring with a needle roller and cage assembly. They are an excellent choice for compact bearing arrangements in applications where hardened and ground raceways can be provided on the shaft. The outer ring includes two integral flanges to guide the bearing axially and an annular groove with one or more lubrication holes to facilitate relubrication.

- High radial load carrying capacity
- High stiffness
- Low cross-sectional height
- Accommodate axial displacement in both directions



Dimensions		
F_w	65 mm	Diameter under rollers
D	78 mm	Outside diameter
C	35 mm	Width
$r_{1,2}$	min. 0.6 mm	Chamfer dimension outer ring




Abutment dimensions		
D_a	max. 74 mm	Diameter of housing abutment
r_a	max. 0.6 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	58.3 kN
Basic static load rating	C_0	146 kN

Fatigue load limit	P_u	18.3 kN
Reference speed		6 300 r/min
Limiting speed		7 000 r/min

Associated seals



Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5, ISO - F6 (F_w)
- Radial internal clearance: table

DESIGN CONSIDERATIONS

- Housing tolerances: table
- Shaft tolerances: Operating clearance