


HK 3520



Drawn cup needle roller bearings are typically used in applications where the housing bore cannot be used as a raceway for a needle roller and cage assembly, but where a very compact and economical bearing arrangement is required. Owing to their large number of rollers, the bearings have a high load carrying capacity and stiffness.

- High radial load carrying capacity
- High stiffness
- Very low cross-sectional height



Dimensions

F_w	35 mm	Diameter under rollers
D	42 mm	Outside diameter
C	20 mm	Width
r	min. 0.8 mm	Chamfer dimension drawn cup (outer ring)

Calculation data

Basic dynamic load rating	C	22.9 kN
Basic static load rating	C_0	46.5 kN
Fatigue load limit	P_u	5.6 kN
Reference speed		7 000 r/min
Limiting speed		8 000 r/min

Associated products

Inner ring IR series	IR 30x35x20.5
Inner ring LR series	LR 30x35x20.5
Radial shaft seal with a low cross-sectional height, single lip	G 35x42x4

Radial shaft seal with a low cross-sectional height, double lip

SD 35x42x4

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table

DESIGN CONSIDERATIONS

- Shaft and housing tolerances: table

AGA BEARINGS