

## HK 2016



Drawn cup needle roller bearings are typically used in applications where the housing bore cannot be used as a raceway for a needle roller and cage assembly, but where a very compact and economical bearing arrangement is required. Owing to their large number of rollers, the bearings have a high load carrying capacity and stiffness.

- High radial load carrying capacity
- High stiffness
- Very low cross-sectional height



| Dimensions |             |                                          |
|------------|-------------|------------------------------------------|
| $F_w$      | 20 mm       | Diameter under rollers                   |
| $D$        | 26 mm       | Outside diameter                         |
| $C$        | 16 mm       | Width                                    |
| $r$        | min. 0.8 mm | Chamfer dimension drawn cup (outer ring) |

### Calculation data

|                           |       |              |
|---------------------------|-------|--------------|
| Basic dynamic load rating | $C$   | 12.3 kN      |
| Basic static load rating  | $C_0$ | 20.4 kN      |
| Fatigue load limit        | $P_u$ | 2.36 kN      |
| Reference speed           |       | 12 000 r/min |
| Limiting speed            |       | 14 000 r/min |

### Associated products

|                                                                 |               |
|-----------------------------------------------------------------|---------------|
| Inner ring IR series                                            | IR 17x20x16.5 |
| Inner ring LR series                                            | LR 17x20x16.5 |
| Radial shaft seal with a low cross-sectional height, single lip | G 20x26x4     |

Radial shaft seal with a low cross-sectional height, double lip

SD 20x26x4

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table

DESIGN CONSIDERATIONS

- Shaft and housing tolerances: table

AGA BEARINGS