

HK 1816



Drawn cup needle roller bearings are typically used in applications where the housing bore cannot be used as a raceway for a needle roller and cage assembly, but where a very compact and economical bearing arrangement is required. Owing to their large number of rollers, the bearings have a high load carrying capacity and stiffness.

- High radial load carrying capacity
- High stiffness
- Very low cross-sectional height



Dimensions

F_w	18 mm	Diameter under rollers
D	24 mm	Outside diameter
C	16 mm	Width
r	min. 0.8 mm	Chamfer dimension drawn cup (outer ring)

Calculation data

Basic dynamic load rating	C	11.2 kN
Basic static load rating	C_0	17.6 kN
Fatigue load limit	P_u	2.04 kN
Reference speed		13 000 r/min
Limiting speed		15 000 r/min

Associated products

Inner ring IR series	IR 15x18x16.5
Inner ring LR series	LR 15x18x16.5
Radial shaft seal with a low cross-sectional height, single lip	G 18x24x3

Radial shaft seal with a low cross-sectional height, double lip

SD 18x24x3

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table

DESIGN CONSIDERATIONS

- Shaft and housing tolerances: table

AGA BEARINGS