


29388 EM


Spherical roller thrust bearings accommodate very heavy axial and considerable radial loads. They have the highest load rating of all thrust bearings, enabling compact, high power density bearing arrangements. By combining two or more spherical roller thrust bearings, it is possible to create a bearing arrangement that is either self-aligning, allowing misalignment of the shaft, or very stiff.



- High load carrying capacity
- Can accommodate combined loads
- Allow misalignment or create very stiff bearing arrangements
- Long service life and low friction
- Separable design



Dimensions		
d	440 mm	Bore diameter
D	680 mm	Outside diameter
H	145 mm	Height
d ₁	≈ 626 mm	Outside diameter of shaft washer end side face
D ₁	≈ 540 mm	Shoulder diameter outer ring
B	49 mm	Width shaft washer or length of shaft washer bore diameter that fits on shaft (bearings with a machined cage)
B ₁	140 mm	Height shaft washer + cage
C	70.5 mm	Height housing washer
s	249 mm	Distance from shaft washer end side face to pressure point
r _{1,2}	min. 6 mm	Chamfer dimension shaft washer



Abutment dimensions

d_a	min. 560 mm	Diameter of shaft abutment
D_a	max. 605 mm	Diameter of housing abutment
r_a	max. 5 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	5 200 kN
Basic static load rating	C_0	19 300 kN
Fatigue load limit	P_u	1 560 kN
Reference speed		530 r/min
Limiting speed		850 r/min
Minimum axial load factor	A	34

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit