

812/1060 M

Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



Dimensions		
d	1 060 mm	Bore diameter
D	1 400 mm	Outside diameter
H	265 mm	Height
d ₁	1 395 mm	Outside diameter shaft washer
D ₁	1 063 mm	Bore diameter housing washer
B	77.5 mm	Height shaft washer
r _{1,2}	min. 9.5 mm	Chamfer dimension housing washer



Abutment dimensions		
d _a	min. 1 340 mm	Abutment diameter shaft
D _a	max. 1 120 mm	Abutment diameter housing
r _a	max. 8 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	12 000 kN
Basic static load rating	C ₀	71 000 kN
Fatigue load limit	P _u	3 650 kN
Reference speed		75 r/min
Limiting speed		150 r/min
Minimum axial load factor	A	400

Included products

Shaft washer	IW-812/1060
Housing washer	OW-812/1060

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions