

## 812/1000 M


Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



| Dimensions       |             |                                  |
|------------------|-------------|----------------------------------|
| d                | 1 000 mm    | Bore diameter                    |
| D                | 1 320 mm    | Outside diameter                 |
| H                | 250 mm      | Height                           |
| d <sub>1</sub>   | 1 308 mm    | Outside diameter shaft washer    |
| D <sub>1</sub>   | 1 012 mm    | Bore diameter housing washer     |
| B                | 75 mm       | Height shaft washer              |
| r <sub>1,2</sub> | min. 9.5 mm | Chamfer dimension housing washer |



| Abutment dimensions |               |                           |
|---------------------|---------------|---------------------------|
| d <sub>a</sub>      | min. 1 260 mm | Abutment diameter shaft   |
| D <sub>a</sub>      | max. 1 060 mm | Abutment diameter housing |
| r <sub>a</sub>      | max. 8 mm     | Fillet radius             |

Calculation data

|                           |                |           |
|---------------------------|----------------|-----------|
| Basic dynamic load rating | C              | 10 200 kN |
| Basic static load rating  | C <sub>0</sub> | 60 000 kN |
| Fatigue load limit        | P <sub>u</sub> | 3 200 kN  |
| Reference speed           |                | 85 r/min  |
| Limiting speed            |                | 170 r/min |
| Minimum axial load factor | A              | 290       |

Included products

|                |             |
|----------------|-------------|
| Shaft washer   | IW-812/1000 |
| Housing washer | OW-812/1000 |

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions