


## 811/500 M

Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



| Dimensions       |             |                                  |
|------------------|-------------|----------------------------------|
| d                | 500 mm      | Bore diameter                    |
| D                | 600 mm      | Outside diameter                 |
| H                | 80 mm       | Height                           |
| d <sub>1</sub>   | 595 mm      | Outside diameter shaft washer    |
| D <sub>1</sub>   | 505 mm      | Bore diameter housing washer     |
| B                | 24 mm       | Height shaft washer              |
| r <sub>1,2</sub> | min. 2.1 mm | Chamfer dimension housing washer |



| Abutment dimensions |             |                           |
|---------------------|-------------|---------------------------|
| d <sub>a</sub>      | min. 592 mm | Abutment diameter shaft   |
| D <sub>a</sub>      | max. 519 mm | Abutment diameter housing |
| r <sub>a</sub>      | max. 2 mm   | Fillet radius             |

Calculation data

|                           |                |           |
|---------------------------|----------------|-----------|
| Basic dynamic load rating | C              | 1 560 kN  |
| Basic static load rating  | C <sub>0</sub> | 9 300 kN  |
| Fatigue load limit        | P <sub>u</sub> | 620 kN    |
| Reference speed           |                | 280 r/min |
| Limiting speed            |                | 560 r/min |
| Minimum axial load factor | A              | 6.919     |

Included products

|                |            |
|----------------|------------|
| Shaft washer   | IW-811/500 |
| Housing washer | OW-811/500 |

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions