

81156 M

Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



Dimensions		
d	280 mm	Bore diameter
D	350 mm	Outside diameter
H	53 mm	Height
d ₁	347 mm	Outside diameter shaft washer
D ₁	283 mm	Bore diameter housing washer
B	15.5 mm	Height shaft washer
r _{1,2}	min. 1.5 mm	Chamfer dimension housing washer



Abutment dimensions		
d _a	min. 346 mm	Abutment diameter shaft
D _a	max. 288 mm	Abutment diameter housing
r _a	max. 1.5 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	680 kN
Basic static load rating	C ₀	3 550 kN
Fatigue load limit	P _u	275 kN
Reference speed		480 r/min
Limiting speed		950 r/min
Minimum axial load factor	A	1.008

Included products

Roller and cage thrust assembly	K 81156 M
Shaft washer	WS 81156
Housing washer	GS 81156

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions