


89444 M


Double row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



Dimensions		
d	220 mm	Bore diameter
D	420 mm	Outside diameter
H	122 mm	Height
d ₁	420 mm	Outside diameter shaft washer
D ₁	225 mm	Bore diameter housing washer
B	41 mm	Height shaft washer
r _{1,2}	min. 6 mm	Chamfer dimension housing washer



Abutment dimensions		
d _a	min. 413 mm	Abutment diameter shaft
D _a	max. 246 mm	Abutment diameter housing
r _a	max. 6 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	2 320 kN
Basic static load rating	C ₀	11 200 kN
Fatigue load limit	P _u	880 kN
Reference speed		340 r/min
Limiting speed		700 r/min
Minimum axial load factor	A	10.035

Included products

Roller and cage thrust assembly	K 89444 M
Shaft washer	WS 89444
Housing washer	GS 89444

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions