

81238 M

Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



Dimensions		
d	190 mm	Bore diameter
D	270 mm	Outside diameter
H	62 mm	Height
d ₁	267 mm	Outside diameter shaft washer
D ₁	194 mm	Bore diameter housing washer
B	18 mm	Height shaft washer
r _{1,2}	min. 2 mm	Chamfer dimension housing washer



Abutment dimensions		
d _a	min. 265 mm	Abutment diameter shaft
D _a	max. 200 mm	Abutment diameter housing
r _a	max. 2 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	695 kN
Basic static load rating	C ₀	2 900 kN
Fatigue load limit	P _u	250 kN
Reference speed		500 r/min
Limiting speed		1 000 r/min
Minimum axial load factor	A	0.673

Included products

Roller and cage thrust assembly	K 81238 M
Shaft washer	WS 81238
Housing washer	GS 81238

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions