

81130 TN

Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



Dimensions		
d	150 mm	Bore diameter
D	190 mm	Outside diameter
H	31 mm	Height
d ₁	188 mm	Outside diameter shaft washer
D ₁	152 mm	Bore diameter housing washer
B	9.5 mm	Height shaft washer
r _{1,2}	min. 1 mm	Chamfer dimension housing washer



Abutment dimensions		
d _a	min. 185 mm	Abutment diameter shaft
D _a	max. 155 mm	Abutment diameter housing
r _a	max. 1 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	212 kN
Basic static load rating	C ₀	1 000 kN
Fatigue load limit	P _u	88 kN
Reference speed		850 r/min
Limiting speed		1 700 r/min
Minimum axial load factor	A	0.08

Included products

Roller and cage thrust assembly	K 81130 TN
Shaft washer	WS 81130
Housing washer	GS 81130

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions