

81226 TN

Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



Dimensions		
d	130 mm	Bore diameter
D	190 mm	Outside diameter
H	45 mm	Height
d ₁	187 mm	Outside diameter shaft washer
D ₁	133 mm	Bore diameter housing washer
B	13 mm	Height shaft washer
r _{1,2}	min. 1.5 mm	Chamfer dimension housing washer



Abutment dimensions		
d _a	min. 181 mm	Abutment diameter shaft
D _a	max. 137 mm	Abutment diameter housing
r _a	max. 1.5 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	380 kN
Basic static load rating	C ₀	1 460 kN
Fatigue load limit	P _u	137 kN
Reference speed		700 r/min
Limiting speed		1 400 r/min
Minimum axial load factor	A	0.171

Included products

Roller and cage thrust assembly	K 81226 TN
Shaft washer	WS 81226
Housing washer	GS 81226

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions