


89416 M


Double row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design



Dimensions		
d	80 mm	Bore diameter
D	170 mm	Outside diameter
H	54 mm	Height
d ₁	170 mm	Outside diameter shaft washer
D ₁	83 mm	Bore diameter housing washer
B	18 mm	Height shaft washer
r _{1,2}	min. 2.1 mm	Chamfer dimension housing washer



Abutment dimensions		
d _a	min. 166 mm	Abutment diameter shaft
D _a	max. 89 mm	Abutment diameter housing
r _a	max. 2.1 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	440 kN
Basic static load rating	C ₀	1 730 kN
Fatigue load limit	P _u	173 kN
Reference speed		900 r/min
Limiting speed		1 800 r/min
Minimum axial load factor	A	0.239

Included products

Roller and cage thrust assembly	K 89416 M
Shaft washer	WS 89416
Housing washer	GS 89416

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions