

81208 TN

Single row cylindrical roller thrust bearings are designed to accommodate heavy axial loads and peak loads in one direction, but not radial loads. They provide a high degree of stiffness and require little axial space. They are mainly used in applications where thrust ball bearings do not have sufficient load carrying capacity. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High axial load carrying capacity
- High stiffness
- Long service life
- Require little axial space
- Separable design

Dimensions

d	40 mm	Bore diameter
D	68 mm	Outside diameter
H	19 mm	Height
d ₁	68 mm	Outside diameter shaft washer
D ₁	42 mm	Bore diameter housing washer
B	5 mm	Height shaft washer
r _{1,2}	min. 1 mm	Chamfer dimension housing washer

Abutment dimensions

d _a	min. 66 mm	Abutment diameter shaft
D _a	max. 43 mm	Abutment diameter housing
r _a	max. 1 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	83 kN
Basic static load rating	C ₀	255 kN
Fatigue load limit	P _u	26.5 kN
Reference speed		1 900 r/min
Limiting speed		3 800 r/min
Minimum axial load factor	A	0.0052

Included products

Roller and cage thrust assembly	K 81208 TN
Shaft washer	WS 81208
Housing washer	GS 81208

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: table, table, values

DESIGN CONSIDERATIONS

- table

BEARING INTERFACES

- Seat tolerances for standard conditions