


NNC 4836 CV




Double row cylindrical roller bearings are designed to accommodate high to very high radial loads in combination with medium to high speeds. The NR assortment includes many designs and variants, such as standard and full complement bearings and also greased and sealed bearings. Depending on the configuration of the outer and inner rings, the bearings are available in locating as well as non-locating designs.

- High to very high radial load carrying capacity
- Low friction
- Long service life



| Dimensions       |             |                                             |
|------------------|-------------|---------------------------------------------|
| d                | 180 mm      | Bore diameter                               |
| D                | 225 mm      | Outside diameter                            |
| B                | 45 mm       | Width                                       |
| d <sub>1</sub>   | ≈ 200 mm    | Shoulder diameter inner ring                |
| D <sub>1</sub>   | ≈ 208.5 mm  | Shoulder diameter outer ring                |
| b <sub>1</sub>   | 7 mm        | Width annular lubrication groove outer ring |
| K                | 4 mm        | Diameter lubrication hole (outer ring)      |
| r <sub>1,2</sub> | min. 1.1 mm | Chamfer dimension (open bearings)           |



| Abutment dimensions |             |                           |
|---------------------|-------------|---------------------------|
| d <sub>a</sub>      | min. 186 mm | Abutment diameter shaft   |
| d <sub>as</sub>     | 193 mm      | Abutment diameter shaft   |
| D <sub>a</sub>      | max. 219 mm | Abutment diameter housing |
| r <sub>a</sub>      | max. 1 mm   | Fillet radius             |

Calculation data

|                           |                |             |
|---------------------------|----------------|-------------|
| Basic dynamic load rating | C              | 297 kN      |
| Basic static load rating  | C <sub>0</sub> | 695 kN      |
| Fatigue load limit        | P <sub>u</sub> | 69.5 kN     |
| Reference speed           |                | 1 200 r/min |
| Limiting speed            |                | 1 500 r/min |
| Minimum load factor       | k <sub>r</sub> | 0.2         |

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal
- Radial internal clearance: table
- Axial internal clearance

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit