


NNC 4920 CV




Double row cylindrical roller bearings are designed to accommodate high to very high radial loads in combination with medium to high speeds. The NR assortment includes many designs and variants, such as standard and full complement bearings and also greased and sealed bearings. Depending on the configuration of the outer and inner rings, the bearings are available in locating as well as non-locating designs.

- High to very high radial load carrying capacity
- Low friction
- Long service life



Dimensions		
d	100 mm	Bore diameter
D	140 mm	Outside diameter
B	40 mm	Width
d ₁	≈ 116.5 mm	Shoulder diameter inner ring
D ₁	≈ 124.5 mm	Shoulder diameter outer ring
b ₁	5 mm	Width annular lubrication groove outer ring
K	3.5 mm	Diameter lubrication hole (outer ring)
r _{1,2}	min. 1.1 mm	Chamfer dimension (open bearings)



Abutment dimensions		
d _a	min. 106 mm	Abutment diameter shaft
d _{as}	111 mm	Abutment diameter shaft
D _a	max. 134 mm	Abutment diameter housing
r _a	max. 1 mm	Fillet radius

Calculation data

Basic dynamic load rating	C	209 kN
Basic static load rating	C ₀	400 kN
Fatigue load limit	P _u	46.5 kN
Reference speed		2 000 r/min
Limiting speed		2 600 r/min
Minimum load factor	k _r	0.25

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal
- Radial internal clearance: table
- Axial internal clearance

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit