

NU 20/670 ECMA/HB1

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High radial load carrying capacity
- Low friction
- Long service life
- Accommodate axial displacement in both directions
- Separable design



Dimensions		
d	670 mm	Bore diameter
D	980 mm	Outside diameter
B	180 mm	Width
D ₁	≈ 890 mm	Shoulder diameter of outer ring
F	746 mm	Raceway diameter of inner ring
r _{1,2}	min. 7.5 mm	Chamfer dimension
s	max. 7 mm	Permissible axial displacement



Abutment dimensions		
da	min. 698 mm	Diameter of spacer sleeve
da	max. 736 mm	Diameter of spacer sleeve
db	min. 752 mm	Diameter of shaft abutment
Da	max. 952 mm	Diameter of housing abutment
ra	max. 6 mm	Radius of fillet

Calculation data

Basic dynamic load rating	C	5 390 kN
Basic static load rating	C ₀	11 000 kN
Fatigue load limit	P _u	750 kN
Reference speed		500 r/min
Limiting speed		800 r/min
Minimum load factor	k _r	0.14
Limiting value	e	0.3
Calculation factor	Y	0.4

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, Normal (inch)
- Radial internal clearance: cylindrical bore, tapered bore
- Axial internal clearance: NUP, NJ + HJ

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit