

NU 12/630 ECMA/HB1

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High radial load carrying capacity
- Low friction
- Long service life
- Accommodate axial displacement in both directions
- Separable design



Dimensions		
d	630 mm	Bore diameter
D	1 150 mm	Outside diameter
B	230 mm	Width
D ₁	≈ 1 005 mm	Shoulder diameter of outer ring
F	751 mm	Raceway diameter of inner ring
r _{1,2}	min. 12 mm	Chamfer dimension
s	max. 13.5 mm	Permissible axial displacement



Abutment dimensions		
da	min. 678 mm	Diameter of spacer sleeve
da	max. 735 mm	Diameter of spacer sleeve
db	min. 757 mm	Diameter of shaft abutment
Da	max. 1 102 mm	Diameter of housing abutment
ra	max. 10 mm	Radius of fillet

Calculation data

Basic dynamic load rating	C	8 580 kN
Basic static load rating	C ₀	13 700 kN
Fatigue load limit	P _u	915 kN
Reference speed		450 r/min
Limiting speed		700 r/min
Minimum load factor	k _r	0.17
Limiting value	e	0.3
Calculation factor	Y	0

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, Normal (inch)
- Radial internal clearance: cylindrical bore, tapered bore
- Axial internal clearance: NUP, NJ + HJ

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit