

NU 10/560 MA

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High radial load carrying capacity
- Low friction
- Long service life
- Accommodate axial displacement in both directions
- Separable design



Dimensions		
d	560 mm	Bore diameter
D	820 mm	Outside diameter
B	115 mm	Width
D ₁	≈ 726 mm	Shoulder diameter of outer ring
F	625 mm	Raceway diameter of inner ring
r _{1,2}	min. 6 mm	Chamfer dimension
s	max. 12.3 mm	Permissible axial displacement



Abutment dimensions		
d _a	min. 583 mm	Diameter of spacer sleeve
d _a	max. 617 mm	Diameter of spacer sleeve
d _b	min. 630 mm	Diameter of shaft abutment
D _a	max. 797 mm	Diameter of housing abutment
r _a	max. 5 mm	Radius of fillet

Calculation data

Basic dynamic load rating	C	2 330 kN
Basic static load rating	C ₀	4 250 kN
Fatigue load limit	P _u	310 kN
Reference speed		750 r/min
Limiting speed		1 000 r/min
Minimum load factor	k _r	0.15
Limiting value	e	0.2
Calculation factor	Y	0.6

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, Normal (inch)
- Radial internal clearance: cylindrical bore, tapered bore
- Axial internal clearance: NUP, NJ + HJ

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit