

NU 2080 ECMA

Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and no flanges on the inner ring, NU design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High radial load carrying capacity
- Low friction
- Long service life
- Accommodate axial displacement in both directions
- Separable design



Dimensions		
d	400 mm	Bore diameter
D	600 mm	Outside diameter
B	118 mm	Width
D ₁	≈ 536 mm	Shoulder diameter of outer ring
F	449 mm	Raceway diameter of inner ring
r _{1,2}	min. 5 mm	Chamfer dimension
s	max. 9.9 mm	Permissible axial displacement



Abutment dimensions		
d _a	min. 418 mm	Diameter of spacer sleeve
d _a	max. 446 mm	Diameter of spacer sleeve
d _b	min. 454 mm	Diameter of shaft abutment
D _a	max. 582 mm	Diameter of housing abutment
r _a	max. 4 mm	Radius of fillet

Calculation data

Basic dynamic load rating	C	2 420 kN
Basic static load rating	C ₀	4 550 kN
Fatigue load limit	P _u	365 kN
Reference speed		950 r/min
Limiting speed		1 400 r/min
Minimum load factor	k _r	0.2
Limiting value	e	0.3
Calculation factor	Y	0.4

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, Normal (inch)
- Radial internal clearance: cylindrical bore, tapered bore
- Axial internal clearance: NUP, NJ + HJ

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit