


NUP 252 MA


Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and one integral flange and one loose flange ring on the inner ring, NUP design bearings can locate the shaft axially in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High radial load carrying capacity
- Low friction
- Long service life
- Locate the shaft axially in both directions
- Separable design



Dimensions		
d	260 mm	Bore diameter
D	480 mm	Outside diameter
B	80 mm	Width
d ₁	≈ 340 mm	Shoulder diameter of inner ring
D ₁	≈ 397 mm	Shoulder diameter of outer ring
F	320 mm	Raceway diameter of inner ring
r _{1,2}	min. 5 mm	Chamfer dimension



Abutment dimensions		
d _a	min. 280 mm	Diameter of spacer sleeve
d _b	min. 344 mm	Diameter of shaft abutment
D _a	max. 460 mm	Diameter of housing abutment
r _a	max. 4 mm	Radius of fillet

Calculation data

Basic dynamic load rating	C	1 170 kN
Basic static load rating	C ₀	1 700 kN
Fatigue load limit	P _u	150 kN
Reference speed		1 400 r/min
Limiting speed		2 000 r/min
Minimum load factor	k _r	0.23
Limiting value	e	0.2
Calculation factor	Y	0.6

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal ($\circ$), P6, Normal (inch)
- Radial internal clearance: cylindrical bore, tapered bore
- Axial internal clearance: NUP, NJ + HJ

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit