


N 326 ECM


Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the inner ring and no flanges on the outer ring, N design bearings can accommodate axial displacement in both directions. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High radial load carrying capacity
- Low friction
- Long service life
- Accommodate axial displacement in both directions
- Separable design



Dimensions		
d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	58 mm	Width
d ₁	≈ 181 mm	Shoulder diameter of inner ring
E	247 mm	Raceway diameter of outer ring
r _{1,2}	min. 4 mm	Chamfer dimension
r _{3,4}	min. 4 mm	Chamfer dimension
s	max. 3.7 mm	Permissible axial displacement



Abutment dimensions		
d _a	min. 147 mm	Diameter of spacer sleeve
d _a	max. 243 mm	Diameter of spacer sleeve
D _a	min. 251 mm	Diameter of housing abutment
D _a	max. 262 mm	Diameter of housing abutment

r_a	max. 3 mm	Radius of fillet
r_b	max. 3 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	720 kN
Basic static load rating	C_0	750 kN
Fatigue load limit	P_u	81.5 kN
Reference speed		2 400 r/min
Limiting speed		3 000 r/min
Minimum load factor	k_r	0.12
Limiting value	e	0.2
Calculation factor	Y	0.6

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, Normal (inch)
- Radial internal clearance: cylindrical bore, tapered bore
- Axial internal clearance: NUP, NJ + HJ

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit