

NJ 2218 ECML


Single row cylindrical roller bearings are designed to accommodate high radial loads in combination with high speeds. Having two integral flanges on the outer ring and one on the inner ring, NJ design bearings can accommodate axial displacement in one direction. An important feature is the separable design, which facilitates mounting and enables the bearing components to be interchanged.



- High radial load carrying capacity
- Low friction
- Long service life
- Locate the shaft axially in one direction
- Separable design



Dimensions		
d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	40 mm	Width
d ₁	≈ 114 mm	Shoulder diameter of inner ring
D ₁	≈ 139.25 mm	Shoulder diameter of outer ring
F	107 mm	Raceway diameter of inner ring
r _{1,2}	min. 2 mm	Chamfer dimension
r _{3,4}	min. 2 mm	Chamfer dimension
s	max. 2.6 mm	Permissible axial displacement



Abutment dimensions		
d _a	min. 101 mm	Diameter of spacer sleeve
d _a	max. 104 mm	Diameter of spacer sleeve
d _b	min. 117 mm	Diameter of shaft abutment

D_a	max. 149 mm	Diameter of housing abutment
r_a	max. 2 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	280 kN
Basic static load rating	C_0	315 kN
Fatigue load limit	P_u	39 kN
Reference speed		4 500 r/min
Limiting speed		7 500 r/min
Minimum load factor	k_r	0.3
Limiting value	e	0.3
Calculation factor	Y	0.4

Associated products

Angle ring	HJ 2218 EC
------------	------------

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal (), P6, Normal (inch)
- Radial internal clearance: cylindrical bore, tapered bore
- Axial internal clearance: NUP, NJ + HJ

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit