

BT4B 331347 AG/HA1

Four-row tapered roller bearings can accommodate combined heavy radial and axial loads at low to moderate speeds. They are used almost exclusively in work roll applications such as rolling mills. NR manufactures four-row tapered roller bearings in TQO and TQI designs, in many variants and with different features.



- Very high radial load carrying capacity
- Accommodate axial loads in both directions
- Axial space-saving solution for roll necks
- Low friction
- Long service life

Design variant/feature	TQO/GWI	
Bore type	Cylindrical with helical groove	
	Dimensions	
	d	406.4 mm Bore diameter
	D	565.15 mm Outside diameter
	B	381 mm Total bearing width over inner rings
	T	381 mm Total bearing width over outer rings
	d ₁	≈ 442 mm Abutment diameter shaft
	D ₁	≈ 507 mm Abutment diameter housing
	r _{1,2}	min. 3.3 mm Chamfer dimension inner ring
	r _{3,4}	min. 1.5 mm Outer ring radius (chamfer)

Calculation data		
Basic dynamic load rating	C	6 050 kN
Basic static load rating	C ₀	15 600 kN

Fatigue load limit	P_u	1 180 kN
Comparative radial load rating	C_F	1 630 kN
Comparative axial load rating	C_{Fa}	264 kN
Thrust factor	K	1.76
Limiting value	e	0.33
Calculation factor	Y_1	2
Calculation factor	Y_2	3
Calculation factor	Y_0	2

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: bearings (Normal and CL7C), inch bearings
- Internal clearance

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit