

BT2B 332501/HA5

NR double row tapered roller bearings are ready-to-mount units, manufactured with a predetermined axial clearance or preload. TDO design bearings have a double row outer ring and two single inner rings that usually have an intermediate ring between them. Their roller sets are arranged back-to-back (O-arrangement), which enables them to accommodate tilting moments. Design variants include features such as a helical groove in the bore or lubrication grooves in the side faces of the bearing rings.



- High radial load carrying capacity
- Accommodate axial loads in both directions
- Relatively high stiffness
- Accommodate tilting moments
- Many variants, including a helical groove in the bore or lubrication grooves in the side faces of the bearing rings
- Ready to mount

Design variant/feature	TDO.1/D	
	Dimensions	
	d	914.4 mm Bore diameter
	D	1 066.8 mm Outside diameter
	T	139.7 mm Total width
	C	101.6 mm Width of outer ring
	d ₁	982.271 mm Shoulder diameter of inner ring (large side face)
	D ₁	1 036.828 mm Raceway diameter of outer ring (large side face)
	r _{1,2}	min. 6.4 mm Chamfer dimension of inner ring
	r _{3,4}	min. 3.3 mm Chamfer dimension of outer ring
	a	339 mm Distance between pressure points

Calculation data

Basic dynamic load rating	C	2 600 kN
Basic static load rating	C ₀	8 000 kN
Fatigue load limit	P _u	520 kN
Limiting value	e	0.4
Calculation factor	Y ₁	1.7
Calculation factor	Y ₂	2.5
Calculation factor	Y ₀	1.6
Comparative radial load rating	C _F	620 kN
Comparative axial load rating	C _{Fa}	248 kN
Thrust factor	K	1.43

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances:
bearings: Normal and CL7C, P5
inch bearings: Normal and CL
- Internal clearance

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit